

RECOATING

MAGIC OIL CLEAN N PREP

Deep cleaner for use in preparation of re-application of PALLMANN® MAGIC OIL 2K

PRODUCT DESCRIPTION:

A concentrated deep-cleaning emulsion specifically formulated for preparing hardwood floors finished with PALLMANN® MAGIC OIL 2K for a maintenance coat.

**FEATURES - BENEFITS:**

- ▶ Concentrate – Adjustable to specific needs
- ▶ Deep-cleaner – Prepares MAGIC OIL'ed floors for maintenance coat
- ▶ Universal formulation – Works on most oiled/waxed floors to prep for MAGIC OIL 2K coating

TECHNICAL DATA:

Packaging:	1 quart plastic bottle
Shelf life:	min. 24 months
Color:	Clear
Mixing ratio:	Normal soiling: 1:10 (1 part Clean to 10 parts water) Heavy Soiling: Undiluted
Working climate:	Min. 60° – 85°F (15° – 25°C); min. 60°F
pH-Value	7 (neutral)
VOC	< 110 g/L

At 70°F and 65% rel. humidity

PREPARATION:**Directions for Use**

1. Remove loose dirt and dust with a mop, broom or vacuum.
2. Shake PALLMANN® MAGIC OIL CLEAN N PREP 2K for 30 seconds.
3. Normal Soiling: Dilute PALLMANN® MAGIC OIL CLEAN N PREP 1 part (clean) 10 parts (water) in clean spray bottle. Lightly mist a 4 x 8 area of the floor, allow product to sit 2 – 3 minutes. Begin buffing floor with a green or red pad. Work in sections small enough to keep the floor wet during the process.
4. Immediately rinse floor with a clean, lint-free towels or cloths. Do not oversaturate the floor during this procedure. Perform a second rinsing of floor to remove all residues.
You may use the PALLMANN® TURBO SCRUBBER to remove residue and for rinsing.
5. Let the floor dry completely prior to re-applying PALLMANN® MAGIC OIL 2K.

Heavy Soiling

Use PALLMANN® MAGIC OIL CLEAN N PREP undiluted following instruction #3 & #4 above. It is important to test one or more small areas to see which cleaning procedure will work best.

Important Notes

- ▶ Floors must be recoated with PALLMANN® MAGIC OIL 2K after deep cleaning with PALLMANN® MAGIC OIL CLEAN N PREP to restore the integrity of the finished surface.
- ▶ Do not use PALLMANN® CLEAN STRONG on a MAGIC OIL 2K finished floor, severe damage will occur!

Storage

Minimum 24 months in original packaging when stored under normal conditions (50-70°F/10-20°C). Tightly reseal opened containers. **Keep from freezing.**

PROTECTION OF THE WORKPLACE AND THE ENVIRONMENT:

Read and follow all safety and environmental precautions and instructions on the packaging label and the Safety Data Sheet (SDS). The SDS is available at www.pallmann.us.

DISPOSAL:

For disposal and recycling, follow the applicable laws and regulations. When possible, avoid or minimize waste generation. Do not allow the material to get into sewers, waterways or unlined ground surfaces. Empty packaging can be recycled.